



E-PACE

TECHNICAL SPECIFICATION
OCTOBER 2020



E-PACE - TECHNICAL SPECIFICATION

	DIESEL		DIESEL MHEV	
POWERTRAIN	D165	D165	D165	D200
Mild Hybrid Electric Vehicle (MHEV)	-	■	■	■
Transmission	Manual	Automatic	Automatic	Automatic
Driveline: All Wheel Drive (AWD) or Front Wheel Drive (FWD)	FWD	AWD	AWD	AWD
Maximum power (PS/kW/rpm)	163/120/3,750	163/120/3,750	163/120/3,750	204/150/3,750
Maximum torque (Nm/rpm)	380/1,500-2,500	380/1,500-2,500	380/1,500-2,500	430/1,750-2,500
Capacity (cc)	1,997	1,997	1,997	1997
No. of cylinders/Valves per cylinder	4/4	4/4	4/4	4/4
Cylinder layout	In-line	In-line	In-line	In-line
Bore/stroke (mm)	83/92.31	83/92.31	83/92.31	83/92.31
Compression ratio (:1)	16.5+/-0.5	16.5+/-0.5	16.5+/-0.5	16.5+/-0.5
PERFORMANCE				
Acceleration (secs) 0-60mph (0-100 km/h)	9.5 (10)	9.2 (9.8)	9.2 (9.8)	7.9 (8.4)
Maximum speed mph (km/h)	128 (206)	124 (200)	124 (200)	131 (211)
BRAKES				
Front type	17" wheels - Single Piston Sliding Caliper, Vented Disc 18" - 21" wheels - Twin Piston Sliding Caliper, Vented Disc		Twin Piston Sliding Caliper, Vented Disc	
Front diameter (mm)	17" wheels - 325 18" - 21" wheels - 349		349	
Rear type	Single Piston Sliding Caliper, Solid Disc		Single Piston Sliding Caliper, Solid Disc	
Rear diameter (mm)	300	300	300	300
Park Brake	Integrated motor-on caliper		Integrated motor-on caliper	

E-PACE – TECHNICAL SPECIFICATION

	DIESEL		DIESEL MHEV	
	D165	D165		D200
WEIGHTS (kg)*				
Unladen weight (EU)**	1,809	1,916		1,952
Unladen weight (DIN)†	1,734	1,841		1,877
Gross Vehicle Weight (GVW)	2,360	2,470		2,470
TOWING (kg)				
Unbraked trailer	750	750		750
Maximum towing	1,600	1,800		2,000
Maximum coupling point (nose weight)	100	100		100
Maximum vehicle and trailer combination	3,960	4,270		4,470
ROOF CARRYING (kg)				
Maximum roof load (including cross bars)	75	75		75

Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90 percent fuel. †Includes full fluids and 90 percent fuel.

E-PACE - TECHNICAL SPECIFICATION

			DIESEL		DIESEL MHEV	
FUEL ECONOMY			D165	D165	D200	
Fuel tank capacity - useable litres	Large		65	65	65	
	Eco		54	54	54	
Diesel Particulate Filter (DPF)			■	■	■	
WLTP*						
WLTP Consumption	Low	mpg (l/100km)	37.3-34.0 (7.6-8.3)	38.8-36.4 (7.3-7.8)	38.4-36.3 (7.4-7.8)	
	Medium	mpg (l/100km)	47.1-41.1 (6.0-6.9)	43.4-39.5 (6.5-7.1)	42.9-39.2 (6.6-7.2)	
	High	mpg (l/100km)	54.1-47.8 (5.2-5.9)	50.7-46.4 (5.6-6.1)	50.3-45.7 (5.6-6.2)	
	Extra High	mpg (l/100km)	45.9-40.3 (6.2-7.0)	42.5-39.2 (6.7-7.2)	42.2-38.2 (6.7-7.4)	
	Combined	mpg (l/100km)	46.9-41.4 (6.0-6.8)	44.3-40.8 (6.4-6.9)	43.9-40.1 (6.4-7.0)	
WLTP CO ₂ Emissions	Combined	(g/km)	158-179	167-182	169-185	

■ Standard.

*WLTP is the new official EU test used to calculate standardised fuel consumption and CO₂ figures for passenger cars. It measures fuel, energy consumption, range and emissions. This is designed to provide figures closer to real-world driving behaviour. It tests vehicles with optional equipment and with a more demanding test procedure and driving profile. Figures are shown as a range under WLTP testing measures. The lowest figures refer to the most economical/lightest set of options. The highest figures refer to the least economical/heaviest set of options. WLTP legislation dictates that where there is <5g CO₂ variance between the lowest and highest figures, only the highest is declared.

E-PACE - TECHNICAL SPECIFICATION

	PETROL MHEV	
	P200	P250
POWERTRAIN		
Mild Hybrid Electric Vehicle (MHEV)	■	■
Transmission	Automatic	Automatic
Driveline: All Wheel Drive (AWD) or Front Wheel Drive (FWD)	AWD	AWD
Maximum power (PS/kW/rpm)	200/147/5,500	249/184/5,500
Maximum torque (Nm/rpm)	320/1,200-4,000	365/1,300-4,500
Capacity (cc)	1,997.34	1,997.34
No. of cylinders/Valves per cylinder	4/4	4/4
Cylinder layout	In-line	In-line
Bore/stroke (mm)	83/92.29	83/92.29
Compression ratio (:1)	10.5+/-0.5	10.5+/-0.5
PERFORMANCE		
Acceleration (secs) 0-60mph (0-100 km/h)	8.0 (8.5)	7.0 (7.5)
Maximum speed mph (km/h)	132 (212)	142 (229)
BRAKES		
Front type	17" wheels - Single Piston Sliding Caliper, Vented Disc 18" - 21" wheels - Twin Piston Sliding Caliper, Vented Disc	Twin Piston Sliding Caliper, Vented Disc
Front diameter (mm)	17" wheels - 325 18" - 21" wheels - 349	349
Rear type	Single Piston Sliding Caliper, Solid Disc	Single Piston Sliding Caliper, Vented Disc
Rear diameter (mm)	300	325
Park Brake	Integrated motor-on caliper	Integrated motor-on caliper

E-PACE - TECHNICAL SPECIFICATION

	PETROL MHEV	
WEIGHTS (kg)*	P200	P250
Unladen weight (EU)**	1,847	1,889
Unladen weight (DIN)†	1,772	1,814
Gross Vehicle Weight (GVW)	2,430	2,430
TOWING (kg)		
Unbraked trailer	750	750
Maximum towing	1,800	1,800
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4,230	4,230
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)	75	75

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90 percent fuel. †Includes full fluids and 90 percent fuel.

E-PACE – TECHNICAL SPECIFICATION

			PETROL MHEV	
FUEL ECONOMY			P200	P250
Fuel tank capacity – useable litres			67	67
Diesel/Gasoline Particulate Filter (DPF/GPF)			■	■
WLTP*				
WLTP Consumption	Low	mpg (l/100km)	23.8-22.4 (11.9-12.6)	23.7-22.4 (11.9-12.6)
	Medium	mpg (l/100km)	32.2-29.6 (8.8-9.5)	32.1-29.6 (8.8-9.5)
	High	mpg (l/100km)	37.3-34.1 (7.6-8.3)	37.1-34.0 (7.6-8.3)
	Extra High	mpg (l/100km)	31.7-28.7 (8.9-9.8)	31.7-28.7 (8.9-9.9)
	Combined	mpg (l/100km)	31.9-29.2 (8.9-9.7)	31.8-29.2 (8.9-9.7)
WLTP CO ₂ Emissions	Combined	(g/km)	200-218	200-218

■ Standard.

*WLTP is the new official EU test used to calculate standardised fuel consumption and CO₂ figures for passenger cars. It measures fuel, energy consumption, range and emissions. This is designed to provide figures closer to real-world driving behaviour. It tests vehicles with optional equipment and with a more demanding test procedure and driving profile. Figures are shown as a range under WLTP testing measures. The lowest figures refer to the most economical/lightest set of options. The highest figures refer to the least economical/heaviest set of options. WLTP legislation dictates that where there is <5g CO₂ variance between the lowest and highest figures, only the highest is declared.

[1]The figures provided are manufacturer's estimates and will be replaced with the official EU test figures as soon as they are available. For comparison purposes only. Real world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories.

E-PACE - TECHNICAL SPECIFICATION

	PETROL MHEV	PETROL PHEV
	P300	P300e
POWERTRAIN		
Mild Hybrid Electric Vehicle (MHEV)	■	-
Transmission	Automatic	Automatic
Driveline: All Wheel Drive (AWD)	AWD	AWD
Maximum power (PS/kW/rpm)	300/221/5,500	309/227/5,500*
Maximum torque (Nm/rpm)	400/1,500-4,500	540/1,600-4,500*
Capacity (cc)	1,997.34	1,498
No. of cylinders/Valves per cylinder	4/4	3/4
Cylinder layout	In-line	In-line
Bore/stroke (mm)	83/92.29	83/92.29
Compression ratio (:1)	10.5+/-0.5	10.5+/-0.5
PERFORMANCE		
Acceleration (secs) 0-60mph (0-100 km/h)	6.6 (6.9)	6.1 (6.5)
Maximum speed mph (km/h)	150 (241)	134 (216)
ELECTRIC MOTOR DATA		
Maximum power (PS/kW)	-	109/80
Maximum torque (Nm)	-	260
BRAKES		
Front type	Twin Piston Sliding Caliper. Vented Disc	Twin Piston Sliding Caliper. Vented Disc
Front diameter (mm)	349	349
Rear type	Single Piston Sliding Caliper. Vented Disc	Single Piston Sliding Caliper. Vented Disc
Rear diameter (mm)	325	325
Park Brake	iEPB. motor on caliper	iEPB. motor on caliper

■ Standard - Not available.

*When combined with electric motor.

E-PACE – TECHNICAL SPECIFICATION

	PETROL MHEV	PETROL PHEV
	P300	P300e
WEIGHTS (kg)*		
Unladen weight (EU)**	1,952	2,173
Unladen weight (DIN)†	1,877	2,098
Gross Vehicle Weight (GVW)	2,450	2,670
TOWING (kg)		
Unbraked trailer	750	750
Maximum towing	1,800	1,600
Maximum coupling point (nose weight)	100	100
Maximum vehicle and trailer combination	4,250	4,270
ROOF CARRYING (kg)		
Maximum roof load (including cross bars)	75	75

*Weights reflect vehicles to standard specifications. Optional extras increase weight. **Includes a 75kg driver, full fluids and 90 percent fuel. †Includes full fluids and 90 percent fuel.

E-PACE - TECHNICAL SPECIFICATION

			PETROL MHEV	PETROL PHEV
			P300	P300e
FUEL ECONOMY				
Fuel tank capacity - useable litres			67	57,6
Gasoline Particulate Filter (GPF)			■	■
EV Range TEH Combined (WLTP*) miles/km			-	34/55
WLTP*				
WLTP Consumption	Low	mpg (l/100km)	23.3-22.8 (12.1-12.4)	-
	Medium	mpg (l/100km)	31.0-29.1 (9.1-9.7)	-
	High	mpg (l/100km)	36.9-34.1 (7.6-8.3)	-
	Extra High	mpg (l/100km)	31.2-28.5 (9.1-9.9)	-
	Combined	mpg (l/100km)	31.3-29.2 (9.0-9.7)	141 (2.0)
WLTP CO ₂ Emissions	Combined	(g/km)	204-218	44

■ Standard - Not available.

*WLTP is the new official EU test used to calculate standardised fuel consumption and CO₂ figures for passenger cars. It measures fuel, energy consumption, range and emissions. This is designed to provide figures closer to real-world driving behaviour. It tests vehicles with optional equipment and with a more demanding test procedure and driving profile. Figures are shown as a range under WLTP testing measures. The lowest figures refer to the most economical/lightest set of options. The highest figures refer to the least economical/heaviest set of options. WLTP legislation dictates that where there is <5g CO₂ variance between the lowest and highest figures, only the highest is declared.

E-PACE - DIMENSIONS

Vehicle Height - 1,648mm

Headroom

Maximum front/rear headroom

With Fixed metal roof fitted 976/974mm

With Panoramic roof fitted 996/970mm

Legroom

Maximum front legroom (Manual) 1,018mm

Maximum front legroom (Automatic) 1,030mm

Maximum rear legroom 872mm

Loadspace Capacity

Height 705mm, Width 1,311mm

Loadspace width between arches 1,057mm

Maximum loadspace volume behind first row

Dry* 1,170 litres, Wet** 1,386 litres

Maximum loadspace volume behind second row

Dry* 494 litres, Wet** 601 litres

Turning Circle

Kerb-to-kerb 11.63m

Wall-to-wall 12m

Turns lock-to-lock 2.31



*Dry: Volume as measured with VDA-compliant solid blocks (200mm x 50mm x 100mm).

**Wet: Volume as measured by simulating the loadspace filled with liquid.

Dimensions were measured with vehicle at unladen weight.