

Park Brake

	DIESEL	
POWERTRAIN	D200 MHEV	
Transmission	Automatic	
Driveline	Rear Wheel Drive (RWD)	
Maximum power (PS/rpm)	204/3,750 - 4,000	
Maximum torque (Nm/rpm)	430/1,750 - 2,500	
Capacity (cc)	1,998	
No. of cylinders/Valves per cylinder	4/4	
Cylinder layout	Inline	
Bore/stroke (mm)	83/92.3	
Compression ratio (:1)	16.5 +/- 0.5	
PERFORMANCE		
Acceleration (secs) 0-60mph (0-100km/h)	7.0 (7.4)	
Maximum speed mph (km/h)	146 (235)	
BRAKES		
Front type	Single Piston Sliding Caliper, Vented Disc	
Front diameter (mm)	325	
Rear type	Single Piston Sliding Caliper, Solid Disc	
Rear diameter (mm)	325	

iEPB, motor on caliper

Some features on images may vary between optional and standard for different model years and due to the impact of Covid-19, many of our images have not been updated to reflect 23/24 model year specifications. Please refer to the car configurator and additionally consult your local Retailer for detailed 23/24 model year specifications and do not base an order on website imagery alone. Jaguar Land Rover Limited is constantly seeking ways to improve the specification, design and production of its vehicles, parts and accessories and alterations take place continually, and we reserve the right to change without notice.

			DIESEL	
WEIGHTS (kg)*			D200 MHEV	
Unladen weight (EU)**			1,722	
Unladen weight (I	DIN)†		1,647	
Gross Vehicle We	ight (GVW)		2,240	
TOWING (kg)				
Unbraked trailer			750	
Maximum towing			1,800	
Maximum couplin	ng point (nose weigh	t)	75	
Maximum vehicle	and trailer combina	tion	4,040	
ROOF CARRYING	G (kg)			
Maximum roof load (including cross bars)		pars)	75	
FUEL ECONOMY				
Fuel tank capacity – useable litres			58	
Diesel Exhaust Fluid (DEF) – useable litres		litres	16	
Diesel Particulate	Filter (DPF)			
WLTP <sup>++</sup>				
	Low	mpg (I/100km)	44.8 - 42.2 (6.3 - 6.7)	
	Medium	mpg (I/100km)	56.5 - 51.4 (5.0 - 5.5)	
WLTP Consumption	High	mpg (I/100km)	68.9 - 61.4 (4.1 - 4.6)	
	Extra High	mpg (l/100km)	58.9 - 52.3 (4.8 - 5.4)	
	Combined	mpg (l/100km)	57.6 - 52.3 (4.9 - 5.4)	
WLTP CO <sub>2</sub> Emissions	Combined	(g/km)	127 - 140	

#### ■ Standard.

<sup>\*</sup>Weights reflect vehicles to standard specifications. Optional extras increase weight. \*\*Includes a 75 kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel. †The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO<sub>2</sub> and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted.

	PETROL		
POWERTRAIN	P250	P300	
Transmission	Automatic	Automatic	
Driveline	Rear Wheel Drive (RWD)	All Wheel Drive (AWD)	
Maximum power (PS/rpm)	250/5,500	300/5,500	
Maximum torque (Nm/rpm)	365/1,300 - 4,500	400/1,500 - 4,500	
Capacity (cc)	1,998	1,998	
No. of cylinders/Valves per cylinder	4/4	4/4	
Cylinder layout	Inline	Inline	
Bore/stroke (mm)	83/92.3	83/92.3	
Compression ratio (:1)	10.5 +/- 0.5	9.5 +/- 0.5	
PERFORMANCE			
Acceleration (secs) 0-60mph (0-100km/h)	6.4 (6.7)	5.6 (5.9)	
Maximum speed mph (km/h)	150 (242)	155 (250)	
BRAKES			
Front type	Single Piston Sliding Caliper, Vented Disc	Single Piston Sliding Caliper, Vented Disc	
Front diameter (mm)	350	350	
Rear type	Single Piston Sliding Caliper, Solid Disc	Single Piston Sliding Caliper, Solid Disc	
Rear diameter (mm)	325	325	
Park Brake	iEPB, motor on caliper	iEPB, motor on caliper	

			PETROL		
WEIGHTS (kg)*			P250	P300	
Unladen weight (EU)**			1,672	1,726	
Unladen weight (DIN)†			1,597	1,651	
Gross Vehicle Weight (GVW)			2,200	2,240	
TOWING (kg)					
Unbraked trailer			750	750	
Maximum towing			1,800	1,800	
Maximum coupling point (nose weight)		t)	75	75	
Maximum vehicle	and trailer combina	tion	4,000	4,040	
ROOF CARRYING	6 (kg)				
Maximum roof load (including cross bars)		pars)	75	75	
FUEL ECONOMY					
Fuel tank capacity – useable litres			61.7	61.7	
Gasoline Particulate Filter (GPF)					
WLTP <sup>††</sup>					
	Low	mpg (l/100km)	25.0 - 23.7 (11.3 - 11.9)	24.1 - 22.6 (11.7 - 12.5)	
)	Medium	mpg (l/100km)	36.2 - 33.2 (7.8 - 8.5)	33.6 - 31.0 (8.4 - 9.1)	
WLTP Consumption	High	mpg (l/100km)	42.8 - 38.7 (6.6 - 7.3)	39.2 - 35.8 (7.2 - 7.9)	
	Extra High	mpg (l/100km)	39.2 - 34.9 (7.2 - 8.1)	35.8 - 32.1 (7.9 - 8.8)	
	Combined	mpg (l/100km)	36.7 - 33.2 (7.7 - 8.5)	34.0 - 31.0 (8.3 - 9.1)	
WLTP CO <sub>2</sub> Emissions	Combined	(g/km)	175 - 193	190 - 207	

#### ■ Standard.

<sup>\*</sup>Weights reflect vehicles to standard specifications. Optional extras increase weight. \*\*Includes a 75 kg driver, full fluids and 90% fuel. †Includes full fluids and 90% fuel. †The figures provided are as a result of official manufacturer's tests in accordance with EU legislation. For comparison purposes only. Real-world figures may differ. CO<sub>2</sub> and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted.

### **XE** - DIMENSIONS

#### **Vehicle Height**

With roof antenna 1,410 mm

#### Headroom

Maximum front/rear headroom with Panoramic roof fitted 941/940 mm Maximum front/rear headroom with fixed metal roof fitted 971/948 mm

#### Legroom

Maximum front legroom 1,055 mm Maximum rear legroom 889 mm

### **Loadspace Capacity**

Height 355 mm, Width 1,123 mm
Loadspace width between arches 791 mm
Maximum loadspace volume behind first row
Dry\* 912 litres (897 on MHEV)
Wet\*\* 1,275 litres (1,236 on MHEV)
Maximum loadspace volume behind second row
Dry\* 285 litres (270 on MHEV)
Wet\*\* 394 litres (356 on MHEV)

#### **Turning Circle**

Kerb-to-kerb 11.58 m Wall-to-wall 11.96 m Turns lock-to-lock 2.58







Dimensions were measured with vehicle at unladen weight.

Vehicles shown are from the Jaguar global range. Specifications, options and availability may vary between markets and should be verified with your local Jaguar retailer.

<sup>\*</sup>Dry: Volume as measured with VDA-compliant solid blocks (200 mm x 50 mm x 100 mm).

<sup>\*\*</sup>Wet: Volume as measured by simulating the loadspace filled with liquid.